



## Swivel-EAZ™ Polyurethane Wheels



### **FEATURES AND BENEFITS**

- Independent swivel surfaces
- Eliminates the need for costly dual-wheel casters
- Non-marking high performance elastomer treads
- Prolongs the life of swivel casters
- Reduces rolling resistance
- Capable of speeds up to 8 MPH
- Minimizes initial start forces
- Carries twice the load of Standard Size wheels with similar tread hardness
- Offered in four different tread hardness and compounds
- Maintenance-free for longer life
- Add 30% to capacity for loads under 3 MPH



Part Number	Diameter	Width	Axle Size	Capacity 70A (lbs) Black	Capacity 80A (lbs) Red	Capacity 95A (lbs) Blue	Capacity 66D (lbs) Gray	Hub Length
SWE-320-FT SWE-320-CRN	3"	2"	1/2"	N/A N/A	560 320	720 400	800 520	2-1/2"
SWE-420-FT SWE-420-CRN	4"	2"	1/2"	500 300	700 400	900 500	1000 650	2-1/2"
SWE-620-FT SWE-620-CRN	6"	2"	1/2"	900 600	1400 900	1900 1100	2200 1300	2-1/2"
SWE-625-FT SWE-625-CRN	6"	2-1/2"	3/4"	900 600	1400 900	1900 1100	2200 1300	3"
SWE-630-FT SWE-630-CRN	6"	3"	3/4"	900 600	1400 900	1900 1100	2200 1300	3-1/2"
SWE-820-FT SWE-820-CRN	8"	2"	1/2"	1400 1100	2300 1800	3000 2400	3500 2700	2-1/2"
SWE-825-FT SWE-825-CRN	8"	2-1/2"	3/4"	1400 1100	2300 1800	3000 2400	3500 2700	3"
SWE-830-FT SWE-830-CRN	8"	3"	3/4"	1400 1100	2300 1800	3000 2400	3500 2700	3-1/2"
SWE-1030-FT SWE-1030-CRN	10"	3"	3/4" – 1-1/2"	2200 1800	3700 2900	4800 3800	5600 4300	3-1/2"

Note: To calculate weight capacities @ 1-3 mph, divide above capacities by 0.70.